



X950R

	Diesel
	Yanmar
	18.5 (25.2) at 3,200 rpm (Stage V)
	3, cast-iron liners
	Indirect
	1,116
	20.4
	Hydrostatic
	Twin Touch Foot Pedals, 2-Wheel Drive
	14.5 (9)
	9.7 (6)
	Standard
	Standard, Hydraulic Traction Assist
	Internal Wet Disc
	Single Lever 2 Function SCV
	20.9
	2 Front Wheel Steer
	72 (183 LH), 61 (155 RH)
	Stamped Steel, Rolled Edges
	Electric Drive Clutch
	Hydraulic
	13 position, 1–4.5 (25–112)
	48 (122) / 54 (137)
	2
	Standard
	Options: Low Dump or High Dump
	Low Dump: 570
	High Dump: 650*
	High Dump: 80.2 (2,037)
	Yes
	2 piece professional high back seat (seat back height 21 in / 53.3 cm), suspension, optional armrest
	Air ride seat
	Low Dump: 133 (3,382)
	High Dump: 135.8 (3,449)
	ROPs folded: 67 (1,706), ROPs up: 82 (2,078)
	76 (1,938)
	Low Dump: 822 (1,812)
	High Dump: 1,014 (2,235) – incl. Hopper
	46 (1,180)
	5.7 (145)
	58 (1,470)
	18 × 8.5-8
	26 × 12-12
	Reverse Implement Option (RIO)



Z994R



Z997R

ZERO TURN MOWER

ENGINE		
Maximum rated power, kW (hp)	18.4 (24.7) at 3,200 rpm (Stage V)	27.5 (37.4) at 2,800 rpm (Stage V)
Displacement, cu in (cm ³)	77.3 (1,267)	100.2 (1,642)
Cylinders	Three	Three
Injection	Indirect	Direct
Lubrication	Full pressure	Full pressure
Cooling	Liquid	Liquid
Air Cleaner	Dry-type, replaceable	Dry-type, replaceable
Fuel Type	Diesel (Stage V compliant)	Diesel (Stage V compliant)
Fuel Tank Capacity, ltr (gal)	43.6 (9.6)	45.5 (12)
ELECTRICAL SYSTEM		
Charge System	75 amp	75 amp
Battery Voltage	12 Volt	12 Volt
Hour Meter	Standard multi-function display	Standard multi-function display
Operator Presence Starting System	Standard	Standard
DRIVE TRAIN		
Hydraulic Pumps	Dual hydrostatic cross boarding	Kanzaki dual-unitised pumps
Wheel Motors	TuffTorq	Parker Ross
Hydraulic Capacity, ltr (gal)	12.1 (2.7) tank capacity	12.1 (2.7) tank capacity
Travel Speed Forward, km/h (mph)	0–16 (0–10.5)	0–18.5 (0–11.5)
Travel Speed Reverse, km/h (mph)	0–8.1 (0–5)	0–8.1 (0–5)
PTO		
Type	Electrical clutch	Hydraulic clutch
Drive	V-belt	Internal wet disc clutch
BRAKES		
Park Brake	Internal wet discs brake integrated in the transmission	Internal caliper wet disc brake integrated in the transmission
Park Brake Actuation	Hand lever	Hand lever
MOWER DECKS		
Available Widths / Type, in (cm)	54 (137) side discharge 60 (152.4) side discharge 60 (152.4) rear discharge	60 (152.4) side discharge 60 (152.4) rear discharge 72 (182.9) side discharge
Deck construction	7-Iron PRO (One-piece stamped steel with reinforcements) – (except for 60 in rear discharge)	Side Discharge: 7-Iron PRO (One-piece stamped steel with reinforcements); Rear discharge: fabricated
Deck thickness	7-gauge (0.179 in, 4.6 mm) stamped steel	Side Discharge: 7-gauge (0.179 in, 4.6 mm) stamped steel
Height-of-Cut Range / Increment, in (cm)	1–5.5 (2.54–14.0) / 0.25 (0.6)	1.5–5.0 (3.8–12.7) / 0.25 (0.6)
BLADES		
Number	Three	Three
WHEELS AND TYRES		
Drive (Rear) Tyres	24 × 12-12	26 × 12-12
Drive (Rear) Tyres – Optional Tweel	24 × 12N12	26 × 12N12
Caster (Front) Wheel Size	13 × 6.5-6 and flat-free design	15 × 6-6 and flat-free design
SEAT TYPE		
Seat	Deluxe Comfort Seat with suspension and armrest Optional: ComfortGlide Seat	Deluxe Comfort Seat with suspension and armrest Optional: ComfortGlide Seat
DIMENSIONS		
Overall Length, in (cm)	89 (226)	96 (244)
Overall Width (chute down), in (cm)	54 in side discharge deck: 69 (175)	60 in side discharge deck: 74 (188) 72 in side discharge deck: 86 (218.4)
Height, in (cm)	ROPs up: 78 (198)	ROPs up 85 (216)
Weight (with Fluids), kg (lb)	54 in side discharge 764 (1,684)	60 in side discharge 805 (1,774) 60 in rear discharge 829 (1,827) 72 in side discharge 835 (1,841)