

Specifications

Model	F2890E		F3090	F3890
	2WD		4WD	
Engine				
Model	Kubota D1105		Kubota D1305	Kubota V1505
Type and Number of Cylinders	Liquid-cooled diesel (3 cyl)		Liquid-cooled diesel (4 cyl)	
Engine gross horsepower	HP (kW)	27.4 (20.4)	30.6 (22.8)	37.3 (27.8)
Rated Revolution	rpm	3000		
Total Displacement	cc	1123	1261	1498
Fuel tank capacity				
	ℓ	61		
Transmission				
Type	HST (F2/R2)			
Max. travel speed	Forward / Reverse	mph (km/h)		
		19.6 / 11		
4WD / 2WD		2WD	4WD	
4WD mode select		N/A	Full-time 4WD or Auto-assist 4WD with dual acting overrunning clutch	
Differential lock		Standard		
Cruise control		Optional		
Steering				
Steering system		Hydraulic power steering		
Tilt steering		Standard		
Turn Assist Brake		Optional		
Tires				
Front		23×10.5-12	24×12-12	
Rear		16×6.5-8	18×9.5-8	
Front		-	24×13-12	
Rear		-	18×9.5-8	
Dimension				
Tread (Front/Rear)	mm (in.)	975 (38.4) / 875 (34.4)		1063 (41.9) / 1020 (40.2)
Wheel base	mm (in.)	1300 (51.2)		
Overall length w/o deck	mm (in.)	2450 (96.5)		
Overall width w/o deck	mm (in.)	1240 (48.8)	1370 (53.9)	
Overall height with Rops	mm (in.)	1985 (78.1)		
ROPS		Standard (ISO21299 and OSHA)		
Weight	kg (lbs.)	755 (1664)	795 (1753)	815(1797)
Mower deck				
Drive system		Shaft drive		
Clutch type		Wet multi discs, hydraulic		
Mounting system		2-point hitch with hydraulic lift cylinders		
PTO revolution	rpm	2530		
Deck tilt angle	Degrees	90		
Deck tilt assist		Standard		
Maintenance				
Air cleaner	Dust indicator	Standard		
	Dual element	Standard		
Fuel Gauge		Displayed in LCD Digital Panel		
Engine Speed		Displayed in LCD Digital Panel		
Hour Meter		Displayed in LCD Digital Panel		
Tachometer		Displayed in LCD Digital Panel		
Water Temperature		Displayed in LCD Digital Panel		
Tool Box		Standard		
Operator				
Seat	Armrest Adjust	Standard		
	Backrest Adjust	Standard		
	Reclining	Standard		
Cup holder		Standard		
Hydraulic				
Rear Hydraulic Outlet (1 spool)		Optional		
Rear Hydraulic Outlet (2 spool)		Optional		

Mower Specifications

Model	2WD		4WD	4WD
	F2890E		F3090	F3890
Cutting width	Side Discharge	mm (in.)	1372 (54) / 1520 (60)	1520 (60) / 1826 (72)
	Rear Discharge	mm (in.)	1520 (60)	1520 (60) / 1826 (72)
Mulching Kit	Side Discharge	mm (in.)	Optional	
	Rear Discharge	mm (in.)	Optional	
Deck Pan	Pressed		1372 (54)	
	Welded	mm (in.)	1520 (60) / 1826 (72)	
Cutting Height	Min/Max	mm (in.)	25 (1) / 129 (5)	
Cutting Height Adjustment		mm (in.)	Each 6.4 (0.25)	
Number of blades			3	

The company reserves the right to change the above specifications without notice.

This brochure is for descriptive purpose only. Please contact your local Kubota dealer for warranty and safety information.

For your safety, KUBOTA strongly recommends the use of a Roll Over Protective Structure (ROPS) and seat belt in almost all applications.

©2014 Kubota Corporation



KUBOTA (U.K.) LIMITED

Dormer Road Thame, Oxfordshire, OX9 3UN.
Phone Thame (01844) 268000 Fax (08702) 429677

Web site: <http://www.kubota.co.uk>